

MYSTIK® NON-DETERGENT
GENERAL PURPOSE OILS



Date 05/18

DESCRIPTION:

Mystik Non-Detergent General Purpose Oils are designed for use in non-critical applications where a general purpose oil is desired. This includes low pressure hydraulic systems such as hydraulic jacks and air compressors requiring a non-detergent type lubricant. They are available in SAE 10W, 20W-20, and 30 viscosity grades. Mystik Non-Detergent General Purpose Oils are not recommended for use in gasoline or diesel engines.

TYPICAL PROPERTIES:

MYSTIK® NON-DETERGENT GENERAL PURPOSE OILS

Material Code	663111002	663112002	663113002
SAE Grade	10W	20W-20	30
ISO Grade (Approx.)	32	68	100
Density, lb/gal at 60°F (Approx.)	7.54	7.6	7.65
Viscosities (Approx.):			
at 100°C, cSt	5.0	8.0	11
at 40°C, cSt	29	62	119
at 210°F, SUS	44	54	—
at 100°F, SUS	165	340	—
Viscosity Index	95	95	95
Flash Point, ASTM D92, °F (°C)	380 (193)	395 (202)	425 (218)
Pour Point, ASTM D97, °F (°C)	-25 (-32)	-10 (-23)	-5 (-20)

NOTE: Consult machinery operator’s manual for proper viscosity grade. For gasoline or diesel engines, consider Mystik JT-8 engine oils.

Mystik is a registered trademark of CITGO Petroleum Corporation.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.