CITGO SUPERGARD® MARINE PLUS 2-CYCLE ENGINE OIL



Date 04/18

DESCRIPTION:

CITGO SUPERGARD Marine Plus 2-Cycle Engine Oil is a licensed NMMA® TC-W3® oil that effectively combats wear, scuffing, deposit build-up, and enhances lubricity to provide longer engine life.

BENEFITS:

- Reduces carbon and deposit build-up on engine parts
- · Helps prevent piston ring sticking
- High film strength for improved lubricity which provides:
 - Increased engine efficiency
 - Excellent scuffing protection of rings and cylinder and reduced bearing wear
 - Cleaner, better-running engines producing less smoke
- · Guaranteed to protect OEM engine warranties

APPLICATIONS:

CITGO SUPERGARD Marine Plus 2-Cycle Engine Oil is recommended for all water-cooled or liquid-cooled 2-cycle engines requiring an NMMA TC-W3, TC-WII® or TC-W® type oil. It may also be used in many air-cooled 2-cycle engine applications requiring API Service Category TC. Recommended for both direct injected and pre-mix systems.

CITGO SUPERGARD Marine Plus 2-Cycle Engine Oil will provide protection for gasoline fueled 2-cycle engines when used at the primary dilution recommended by the original equipment manufacturer.

Consult owners manual for Fluid Specification.

TYPICAL PROPERTIES:

CITGO SUPERGARD® MARINE PLUS 2-CYCLE ENGINE OIL

Material Code	621602001
Gravity, ASTM D4052, °API Density, lb/gal at 60°F Flash Point, PMCC, ASTM D93, °F (°C) Flash Point, COC, ASTM D92, °F (°C) Viscosity, ASTM D445, cSt at 40°C cSt at 100°C ASTM D2161, SUS at 100°F SUS at 210°F Viscosity Index, ASTM D2270 Pour Point, ASTM D97, °F (°C) Appearance, Color Sulfated Ash, ASTM D874, %	31.5 7.23 178 (81) ⁽¹⁾ 197 (92) 32.0 5.9 163 46 130 -38 (-39) Blue/Green <0.004
Total Base Number, ASTM D2896, mgKOH/g	8.6

NOTE

(1) Combustible liquid

CITGO and SUPERGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.