



**THE
GOOD
STUFF**

SHP FE® Diesel Engine Oil

Kendall SHP FE (Fuel Economy) Diesel Engine Oil is a premium quality, full-synthetic API FA-4 engine oil developed for fuel economy benefits in 2017 and newer engines where FA-4 is specified.

SHP FE is formulated with the highest quality synthetic base stocks and a proprietary low-SAPS additive package to provide outstanding engine protection in diesel engines specifying FA-4. This additive enhancement provides increased engine protection of critical engine parts, despite lower HTHS requirements of FA-4.

SHP FE has excellent soot dispersancy to protect against abrasive wear and soot-induced oil thickening, and to ensure good low-temperature pumpability even with highly soot-laden oil. It provides excellent bearing corrosion protection and protects against sludge and varnish formation. The synthetic blend formulation provides enhanced thermal stability at high temperatures and improved low-temperature properties compared with conventional diesel engine oils.

SHP FE meets or exceeds the performance requirements of API Service Category FA-4, SN and is approved under the latest OEM specifications for use in low-emission diesel engines. It is formulated for use in diesel engines operating on diesel fuels with sulfur content up to 500 ppm.

Applications

- On-highway diesel trucks recommending FA-4 to meet 2017 emissions standards
- Mixed fleets with diesel and gasoline fueled engines

SHP FE is licensed or OEM-certified for:

- API Service FA-4, SN
- Cummins CES 20087
- Detroit Diesel DFS 93K223

**Premium Full
Synthetic API
FA-4 Diesel
Engine Oil;
Formulated for
Fuel Economy**



Features/Benefits

- Excellent protection for newer low-emission diesel engines and older diesel engines
- Specially formulated to protect exhaust aftertreatment systems
- Outstanding soot control for protection against abrasive wear and soot-induced oil thickening
- Outstanding resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust and bearing corrosion
- Excellent low-temperature pumpability with soot-laden oil
- High shear stability
- Good resistance to foaming and aeration

SHP FE[®] Diesel Engine Oil

Typical Properties	
SAE Grade	5W-30
Specific Gravity @ 60°F	0.8540
Density, lbs/gal @ 60°F	7.11
Color, ASTM D1500	3.4
Flash Point (COC), °C (°F)	226 (439)
Pour Point, °C (°F)	-45 (-49)
Viscosity, Kinematic	
cSt @ 40°C	57
cSt @ 100°C	9.9
Viscosity Index	155
Cold Cranking Viscosity, cP @(°C)	5060 (-30)
High-Temp/High-Shear Viscosity, cP @ 150°C	3.0
Sulfated Ash, ASTM D874, wt %	.95
Total Base Number (TBN), ASTM D2896	10.1
Zinc, wt %	0.0823

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

11-16-2017

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

©Phillips 66 Company. Kendall[®] and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.