



VP® Street Legal Motor Oil

Synthetic dexos® Formula

DESCRIPTION

STREET LEGAL™ Synthetic dexos1™ Gen 2 Motor Oil is formulated with select synthetic base oils and a state-of-the-art additive system to deliver trusted engine protection and peak vehicle performance. Synthetic dexos® Motor Oil provides added resistance to sludge formation and varnish deposits during stop-and-go driving and maintains outstanding wear protection under severe driving conditions.

Street Legal Synthetic dexos® Motor Oil is available in SAE grades 0W-20 and 5W-30 and exceeds new car warranty requirements as defined by ILSAC standard GF-5, API classification Resource Conserving SN and approved and licensed for General Motors dexos1™ Gen 2 specification.

PERFORMANCE BENEFITS

- Special chemistry minimizes low speed pre-ignition (LSPi)
- Excellent wear protection for critical engine components
- Ultimate low-temperature engine protection and performance
- Maintains maximum engine protection under severe operating conditions
- Protects vehicle emission systems
- Delivers optimum fuel economy

PRODUCT APPLICATION

Recommended for turbo-charged or naturally aspirated gasoline-powered and flex-fuel passenger cars, hybrid vehicles, light-trucks and sport utility vehicles and fleets requiring:

ILSAC GF-5 & API Service Category Resource Conserving SN (API License number 3233)

Chrysler; MS-6395 (Revision S)

Ford WSS-M2C946A (5W-30)

General Motors dexos1™ Gen 2 (License numbers 0W-20 D10645HI161 & 5W-30 D10646HI161)

Backward compatible and supersedes General Motors GM-LL-A-025, GM4718M & GM6094M (obsolete)

Typical Physical Properties			
Property	Method	0W-20	5W-30
SAE Grade		0W-20	5W-30
Item Number		VP3202010	VP3253010
General Motors Performance		dexos1™	dexos1™
Viscosity, cSt @40°C	D-445	44.8	63.9
Viscosity, cSt @100°C	D-445	8.4	11.0
Viscosity Index	D-2270	169	167
Specific Gravity, @60°F	D-1250	0.846	0.849
Flash Point, COC, °C(°F)	D-92	230 (446)	232 (450)
Pour Point, °C(°F)	D-97	-42 (-44)	-36 (-33)
CCS, cP, maximum @-30°C	D-5293	5600 (-35°C)	4900
NOACK Volatility @ 700°F, % loss	D-5800	<13	<13
Total Base Number (TBN)	D-2896	8.5	8.5
Sulfated Ash, wt.%	D-4929	0.92	0.92

Minor variations in physical test results may occur through normal manufacturing

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

© Copyright 2017 Maverick Performance Products, LLC. All rights reserved.



VP® is a registered trademark of VP Racing Fuels, Inc. VP Lubricants are produced in the U.S.A. for VP Racing Fuels, Inc. by Maverick Performance Products, LLC, authorized manufacturer, reseller, and licensee.